

IEEE Std C37.40™-2003(R2009)

(Revision of
IEEE Std C37.40-1993)

Errata to IEEE Standard Service Conditions and Definitions for High-Voltage Fuses, Distribution Enclosed Single-Pole Air Switches, and Accessories

Sponsor

Switchgear Committee

of the

IEEE Power Engineering Society*Correction Sheet***Issued 30 March 2009**

Copyright © 2009 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved.
Published 2009. Printed in the United States of America.

This correction sheet may be freely reproduced and distributed in order to maintain the utility and currency of the underlying Standard. This correction sheet may not be sold, licensed or otherwise distributed for any commercial purposes whatsoever. The content of this correction sheet may not be modified. This information has been incorporated into the second printing of IEEE Std C37.40-2003.

Page 5, Table 1—Limits of temperature and temperature rise for components and materials where the rated maximum application temperature for the device is 40 °C or less, *should be replaced with the following:*

Table 1—Limits of temperature and temperature rise for components and materials where the rated maximum application temperature for the device is 40 °C or less

Component or material ^{a,b}	Maximum value of	
	Temperature °C	Temperature rise °C
a) Contacts in air or other insulating gasses		
1) Spring-loaded contacts (copper or copper alloy)		
– Bare	75	35
– Tin coated	95	55
– Silver or nickel coated	105	65
– Other coatings ^a		
2) Bolted contacts or equivalent (copper, copper alloy and aluminum alloy)		
– Bare	90	50
– Tin coated	105	65
– Silver or nickel coated	115	75
– Other coatings ^a		
b) Contacts in liquid insulating material (copper or copper alloy)		
1) Spring-loaded contacts		
– Bare	80	40
– Silver, tin, or nickel coated	90	50
– Other coatings ^a		
2) Bolted contacts		
– Bare	80	40
– Silver, tin, or nickel coated	100	60
– Other coatings ^a		
c) Bolted terminals in air ^c		
– Bare	90	50
– Silver, tin, or nickel coated	105	65
– Other coatings ^a		
d) Metal parts acting as springs ^d		
e) Materials used as insulation and metal parts in contact with insulation of following classes:		
Bone fiber	70	30
90	90	50
105	105	65
130	130	90
155	155	115
180	180	140
220	220	180
Over 220 ^e		

^aIf the manufacturer uses coatings other than those indicated in this table, the properties of these materials should be taken into consideration.

^bWhere engaging contact surfaces have different coatings, the permissible temperatures and temperature rises shall be those of the component having the lowest values permitted.

^cThe temperature of a terminal should be no higher than that of the nearest device contact also subject to temperature limits covered by this table.

^dThe temperature or the temperature rise should not reach such a value that the elasticity of the metal is impaired.

^eLimited only by the requirement not to cause any damage to surrounding parts.