

IEEE Standards Interpretation for IEEE Std 1482.1™-1999 IEEE Standard for Rail Transit Vehicle Event Recorders

Copyright © 2005 by the Institute of Electrical and Electronics Engineers, Inc. 3 Park Avenue New York, New York 10016-5997 USA All Rights Reserved.

This is an interpretation of IEEE Std 1482.1-1999.

Interpretations are issued to explain and clarify the intent of a standard and **do not** constitute an alteration to the original standard. In addition, interpretations are not intended to supply consulting information. Permission is hereby granted to download and print one copy of this document. Individuals seeking permission to reproduce and/or distribute this document in its entirety or portions of this document must contact the IEEE Standards Department for the appropriate license. Use of the information contained in this document is at your own risk.

IEEE Standards Department Copyrights and Permissions 445 Hoes Lane, Piscataway, New Jersey 08855-1331, USA

January 2005

Interpretation Request #1

Topic: Crashworthiness **Relevant Clause:** 4.5, Table 3

In Standard IEEE 1482.1-1999, Clause 4.5 Crashworthiness. Table 3 - Crashworthiness requirements the following is mentioned:

Fire: 650°C (1200°F) for 30 minutes, followed by 300°C (570°F) for 60 minutes, followed by 100°C (212°F) for 5 hours.

How should this procedure in reality be performed? Is it meant as follows:

Apply a temperature (fire) of 650°C for 30 minutes, immediately after that continuing with a fire of 300°C for 60 minutes, immediately followed by a fire of 100°C for 5 hours; or Apply a temperature (fire) of 650°C for 30 minutes. Cooling (naturally) down to 300°C and continuing with a fire of 300°C for 60 minutes, cooling down (naturally) to 100°C and continuing with a fire of 100°C for 5 hours; or as similarly requested for Flight Data Recorders and/or Cockpit Voice Recorders:

Apply a temperature (fire) of 650°C for 30 minutes. Restore a stable internal temperature equivalent to that reached after operation at ambient pressure and temperature of 25°C. Apply a fire of 300°C for 60 minutes. Restore a stable internal temperature equivalent to that reached after operation at ambient pressure and temperature of 25°C. Apply a fire of 100°C for 5 hours.

Interpretation Response #1

It is the Committee's interpretation that the natural reading of the text corresponds to your first suggested interpretation, which is "Apply a temperature (fire) of 650°C for 30 minutes, immediately after that continuing with a fire of 300°C for 60 minutes, immediately followed by a fire of 100°C for 5 hours."

Interpretation Request #2

Topic: Type and hardness of steel **Relevant Clause:** Table 3

In the standard mentioned, Table 3 requires a penetration test that should be performed with a "23 kg weight with a protruding 6.4 mm diameter steel pin dropped from a height of 1.5 m."

What type of steel should be used? What hardness should this steel have?

Interpretation Response #2

The standard has no requirements for the type or hardness of the steel. Therefore, you are free to select the material and hardness of your choice, insofar as this standard is concerned.

A typical approach would be to select a pin that has no substantial deformation after the test, but this is not a requirement of the standard.