

---

# Table of Contents

<b>Introduction</b> .....	xv
<b>Acronyms and Abbreviations</b> .....	xvii
<b>Chapter 1 Background and History</b> .....	1
What is an IEEE standard? .....	1
The 802.15 family .....	2
Why 802.15.3? .....	4
History of 802.15.3 .....	6
<b>Chapter 2 802.15.3 applications</b> .....	13
The high-rate WPAN theme .....	13
Still image applications .....	14
Telephone quality audio applications .....	16
High quality audio applications .....	17
Gaming applications .....	18
Video and multimedia applications .....	19
<b>Chapter 3 Overview of the IEEE 802.15.3 standard</b> .....	23
Elements of the 802.15.3 piconet .....	25
PHY overview .....	28
Starting a piconet .....	31
The superframe .....	32
Joining and leaving a piconet .....	34
Connecting with other devices .....	35
Dependent piconets .....	36
Obtaining information .....	39
Power management .....	40
System changes .....	43
Implementation cost and complexity .....	44

---

<b>Chapter 4 MAC functionality</b> . . . . .	47
MAC terminology in IEEE Std 802.15.3 . . . . .	47
Frame formats . . . . .	49
Piconet timing and superframe structure . . . . .	51
Interframe spacings. . . . .	53
Contention access period (CAP). . . . .	55
Channel time allocation period (CTAP). . . . .	56
Comparing the contention access methods. . . . .	60
Guard time . . . . .	63
The role of the PNC . . . . .	66
Starting a piconet . . . . .	66
Handing over control . . . . .	66
Ending a piconet . . . . .	72
Joining and leaving the piconet . . . . .	73
Association . . . . .	74
Broadcasting piconet information. . . . .	77
Disassociation. . . . .	78
Assigning DEVIDs . . . . .	80
Managing bandwidth . . . . .	81
Acknowledgements. . . . .	81
Asynchronous data . . . . .	87
Stream connections. . . . .	92
Fragmentation/defragmentation . . . . .	96
Retransmissions and duplicate detection . . . . .	99
Power management . . . . .	100
Common characteristics of the SPS modes . . . . .	104
Analyzing power save efficiencies . . . . .	107
Switching PM modes . . . . .	110
Managing SPS sets . . . . .	114
DSPS mode. . . . .	118
Allocating channel time for DSPS DEVs. . . . .	119
PSPS mode . . . . .	124
APS mode. . . . .	126
Changing piconet parameters . . . . .	128
Beacon announcements . . . . .	129
Dynamic channel selection. . . . .	132

---

---

Changing the PNID or BSID . . . . .	134
Moving the beacon or changing the superframe duration . . . . .	136
Finding information . . . . .	138
Probe . . . . .	139
Announce . . . . .	143
PNC Information . . . . .	145
Channel status . . . . .	148
PNC channel scanning . . . . .	150
Remote scan . . . . .	152
Piconet services . . . . .	154
Other capabilities . . . . .	157
Transmit power control . . . . .	157
Multirate capabilities . . . . .	159
Extensibility of the standard . . . . .	160
Example of the life cycle of a DEV . . . . .	162
<b>Chapter 5 Dependent piconets . . . . .</b>	<b>165</b>
Introduction . . . . .	165
Starting a dependent piconet . . . . .	168
Parent PNC ceasing operations with dependent piconets . . . . .	174
Parent PNC stopping a dependent piconet . . . . .	176
Handing over PNC responsibilities in a dependent piconet . . . . .	177
<b>Chapter 6 Security . . . . .</b>	<b>187</b>
Introduction and history . . . . .	187
Security modes and policies . . . . .	190
Security services provided in mode 1 . . . . .	191
Security policies . . . . .	193
Symmetric key security suite . . . . .	195
Overview of AES CCM . . . . .	195
Key distribution . . . . .	197
Security information . . . . .	199
<b>Chapter 7 2.4 GHz PHY . . . . .</b>	<b>203</b>
Overview . . . . .	203
General PHY requirements . . . . .	205

---

---

Channel plan . . . . .	205
Timing issues . . . . .	206
Miscellaneous PHY requirements . . . . .	213
PHY frame format . . . . .	213
Stuff bits and tail symbols . . . . .	214
Frame format . . . . .	215
PHY preamble . . . . .	217
Data size restrictions . . . . .	219
Modulation . . . . .	220
Receiver performance . . . . .	224
Transmitter performance . . . . .	228
Regulatory and requirements . . . . .	233
Delay spread performance . . . . .	234
Mitigating the effects of delay spread . . . . .	236
Fading channel model used for 802.15.3 . . . . .	237
Defining delay spread performance . . . . .	239
Delay spread measurements . . . . .	240
Radio architectures . . . . .	244
Superheterodyne . . . . .	245
Direct conversion . . . . .	248
Walking IF . . . . .	250
Low IF . . . . .	253
Summary of radio architectures . . . . .	256
<b>Chapter 8 2.4 Interfacing to 802.15.3 . . . . .</b>	<b>257</b>
The PIBs and their interface . . . . .	261
MLME SAP . . . . .	262
PLME SAP . . . . .	265
MAC SAP . . . . .	265
PHY SAP . . . . .	266
The FC SL . . . . .	268
<b>Chapter 9 2.4 Coexistence mechanisms . . . . .</b>	<b>271</b>
Introduction . . . . .	271
Coexistence techniques in 802.15.3 . . . . .	271
Passive scanning . . . . .	273

---

---

The ability to request channel quality information . . . . .	273
Dynamic channel selection . . . . .	273
Link quality and RSSI . . . . .	274
Channel plan that minimizes channel overlap . . . . .	274
Transmit power control . . . . .	275
Lower impact transmit spectral mask . . . . .	275
Neighbor piconet capability . . . . .	276
Coexistence results . . . . .	278
Assumptions for coexistence simulations . . . . .	278
BER calculations . . . . .	280
802.11b and 802.15.3 . . . . .	282
802.15.1 and 802.11 FHSS overlapping with 802.15.3 . . . . .	288
<b>Summary</b> . . . . .	<b>291</b>
<b>References</b> . . . . .	<b>295</b>
<b>Glossary</b> . . . . .	<b>299</b>
<b>Index</b> . . . . .	<b>305</b>